

THERMAL INSULATION

Ceramic Fibre Insulation Paper



Thermal insulation for kiln, furnace and maintenance enquiries. Confirm fibre grade, density, service temperature and handling information for the exact supplied material.

Unit for enquiry: each | Product range

Product range reference. Colour and supplied configuration are confirmed with your quotation.

PRODUCT DETAILS

Width	1220 mm
Thickness	3 mm
Supply lengths	1 m piece / 15 m box

TYPES / CONFIGURATIONS

Listed size | Custom requirement enquiry

This is a Beccentric product information and selection sheet. It is not a certified engineering drawing or a guarantee of stock. Confirm the exact product, compatibility and operating limits before ordering.

Specify your requirement

Ceramic Fibre Insulation Paper

The choices below help prepare an enquiry. Other sizes and identification assistance can be requested. Not every combination is available.

Size / pack configuration	1000 x 1220 x 3 mm, 15000 x 1220 x 3 mm
Required service temperature (deg C)	Continuous and peak temperatures
Required density / grade	Include existing specification
Equipment / application	Kiln, furnace, lining or seal duty

INCLUDE WITH YOUR ENQUIRY

Include size / pack configuration, required service temperature (deg c), required density / grade, equipment / application, quantity, photographs and required date.

Quantity: _____ Required date: _____

Company / RFQ reference: _____

Exact replacement only / alternative for approval: _____

CONTACT & DOCUMENTATION

[View this product and choose specifications at beccentric.net](#)

WhatsApp Mary: +263 780 864 277

WhatsApp Tino: +263 779 098 357

Email: sales@beccentric.net

Request a drawing, material certificate, food-contact declaration or safety data sheet when your application requires one. These documents relate to the exact product quoted.

Reference basis: Van Tuyl product reference. Compiled 25 September 2026. Supplier material is used to identify the range; Beccentric handles your enquiry.