

MODULAR CONVEYOR BELTS

MW25 Flush Grid Modular Conveyor Belt



Flush grid belt for conveyor replacement and new application enquiries. Match the 25 mm pitch, material and sprockets; similar series names do not guarantee interchangeability.

Unit for enquiry: metre | Reference: MW25

Product range reference. Colour and supplied configuration are confirmed with your quotation.

PRODUCT DETAILS

Series	MW25
Pitch	25 mm
Surface	Flush grid
Open area	40%
Width construction	25 mm width increments; final assembled width to be checked

TYPES / CONFIGURATIONS

Flush grid

This is a Beccentric product information and selection sheet. It is not a certified engineering drawing or a guarantee of stock. Confirm the exact product, compatibility and operating limits before ordering.

Specify your requirement

MW25 Flush Grid Modular Conveyor Belt

The choices below help prepare an enquiry. Other sizes and identification assistance can be requested. Not every combination is available.

Belt width (mm)	Enter your dimensions / reference, or ask for help identifying the item.
Endless length / cut length (mm)	State length and whether endless or open
Required material	Polypropylene (PP), Polyethylene (PE), Acetal (POM)
Supply / joint arrangement	Endless, Open length, Mechanical fastener enquiry
Application / temperature / load	Product conveyed, operating temperature and cleaning conditions
Flights / side guards / inserts	State required attachments
Sprocket / shaft details	Tooth count, bore and matching series

INCLUDE WITH YOUR ENQUIRY

Include belt width (mm), endless length / cut length (mm), required material, supply / joint arrangement, application / temperature / load, flights / side guards / inserts, sprocket / shaft details, quantity, photographs and required date.

Quantity: _____ Required date: _____

Company / RFQ reference: _____

Exact replacement only / alternative for approval: _____

CONTACT & DOCUMENTATION

[View this product and choose specifications at beccentric.net](https://www.beccentric.net)

WhatsApp Mary: +263 780 864 277

WhatsApp Tino: +263 779 098 357

Email: sales@beccentric.net

Request a drawing, material certificate, food-contact declaration or safety data sheet when your application requires one. These documents relate to the exact product quoted.

Reference basis: Belting Edge MW technical data sheet: MW25 Flush Grid Modular. Compiled 25 September 2026. Supplier material is used to identify the range; Beccentric handles your enquiry.