

STAINLESS FASTENERS

Stainless Steel Nuts



Fastener sourcing by thread, length, material and strength designation. Provide inside dimensions for U-bolts and the complete grade where specified.

Unit for enquiry: each | Product range

Supplier catalogue image; confirm the exact supplied configuration.

PRODUCT DETAILS

Thread systems	Metric / UNC / UNF
Material families	A2 / A4; 304 / 316
Strength	Specify required fastener property class

TYPES / CONFIGURATIONS

Hex nut | Nyloc nut | Lock nut | Dome nut

This is a Beccentric product information and selection sheet. It is not a certified engineering drawing or a guarantee of stock. Confirm the exact product, compatibility and operating limits before ordering.

Specify your requirement

Stainless Steel Nuts

The choices below help prepare an enquiry. Other sizes and identification assistance can be requested. Not every combination is available.

Thread size	M6, M8, M10, M12, M16, M20, M24
Thread system	Metric, UNC, UNF
Length / U-bolt dimensions (mm)	Length, inside width and height
Required grade	A2-70, A4-70, A4-80, 304, 316

INCLUDE WITH YOUR ENQUIRY

Confirm thread size, thread system, length / u-bolt dimensions (mm), required grade, quantity and required date. Send existing part markings or a drawing when replacing a component.

Quantity: _____ Required date: _____

Company / RFQ reference: _____

Exact replacement only / alternative for approval: _____

CONTACT & DOCUMENTATION

[View this product and choose specifications at beccentric.net](#)

WhatsApp Mary: +263 780 864 277

WhatsApp Tino: +263 779 098 357

Email: sales@beccentric.net

Request a drawing, material certificate, food-contact declaration or safety data sheet when your application requires one. These documents relate to the exact product quoted.

Reference basis: Natal Stainless Steel profile, p. 12. Compiled 25 September 2026. Supplier material is used to identify the range; Beccentric handles your enquiry.